HN198DP

LCD Panel	Display size	19" (48,26 cm)
	Panel Type	Active Matrix TFT
	Brightness	250 cd/m² (typ.)
	Contrast	700:1 (typ.)
	Pixel pitch	0.294(H)*0.294(V) mm
	Resolution (H x V)	SXGA 1280 x 1024
	Response time	8 ms (typ.)
	View angles LR,UD	H/V 150°/135°
	Display colors	16.2M Colors
	Color	9300K, 6500K, User Mode
	Display Surface	Anti-Glare
Input	Input 1	D-Sub, Audio
	Input 2	DVI-D
	Input 3	
Output	Output 1	
	Output 2	
	Headphone	
	Speakers	1W x 2
Power	Supply	AC 100~240V, 50~60Hz
	Consumption	37 W (typ.)
Operating Condition	Temperature	5 ~ 35℃
	Humidity	10 ~ 85%
Physical	Dimension (W*D*H)	417 x 225 x 445 mm
	Packing dimension (W*D*H)	490 x 175 x 522 mm
	Net weight	5,7 kg
	Gross weight	7,2 kg
	Tilt	0°~ 20°
	Kensington Lock	✓
	VESA mounting	VESA Standard, 100mm
Controls	Front control	Auto, Vol(-), Power/LED, Vol(+), Menu
	On screen display	EN, SC, TC, DE, FR, IT, ES, JS
Certification	Safety	UL/CUL, CB, GS, CCC, BSMI, FCC, CE
	Emission	TCO03
	Power saving	EPA Energy Star
Extras 1		Height Adjustable
Extras 2		Pivot
Extras 3		Swivel base
Accessories		powercord, VGA cable, audio cable, users manual (CD), quickstart

Specifications are subject to change without notice. Error accepted.

HANNspree Europe GmbH
Siemensring 66
47877 Willich
GERMANY
Tel: +49 (0)2154/95 323-0
Fax: +49 (0)2154/95 323-123
http://www.hannsg.com
info.europe@hannspree.com

GO BEYOND